



Transmission oils - Total drive line

Eurol Fultrasyn 75W-90 GL4/5

Fully synthetic oil for manual gearboxes and final drives

Description

Eurol Fultrasyn 75W-90 is a fully synthetic, universal transmission/gear oil which can be used in both manual gearboxes as well as in final drives and where an API GL 3, 4 or 5 specification is required. By this, the oil offers excellent possibilities for reducing stock.

Eurol Fultrasyn 75W-90 is a fully synthetic oil and can be used in the complete drive line. The special additives in this product reduce fuel consumption and eliminate shifting problems.

Eurol Fultrasyn 75W-90 is fully compatible with synchromesh gearboxes and ensures easy shifting, even at very low temperatures.

Because of this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures, the oil is protected against thermal oxidation.

Eurol Fultrasyn 75W-90 shows excellent EP (Extreme Pressure) characteristics to cope with high loads and vibrations. Viscosity drop caused by high loads is minimal, so that the right viscosity is guaranteed, even at prolonged drain intervals.

Performance level

- API GL 4/5
- API MT-1

Recommended for use

- MAN 342 Typ M3
- MAN 342 Typ S1
- MAN 341 Typ E3
- MAN 341 Typ Z2
- DTFR 12B140 (MB 235.8)
- ZF TE-ML 02B/05B/07A/12B/12/12N/16F/17B/19C/21B
- DETROIT DIESEL DFS93K219.01
- Arvin Meritor 076-N
- Mack GO-J
- IVECO
- MIL-PRF-2105E
- Volvo 97312
- Scania STO 1:0
- Renault (Note Technique B0032/2 Annex 3)
- DAF
- SAE J2360
- Scania STO 1:1G
- Scania STO 2:0A FS

Physical properties

Colour	Yellow	
Density at 20°C	0.87 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	95.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	16.4 cSt	ASTM D 445
Viscosity Index	185	ASTM D 2270
Flash point	211 °C	ASTM D 93
Pour point	-54 °C	ASTM D 97

Article number E110076
Version 3.3, 21-11-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.